



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

SDS n° : FP11268

POLYCOR ISO BR

Page 1 / 22

Former date 30-Nov-2016

Revision date 08-Sep-2017

Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	POLYCOR ISO BR
Chemical Name	Gel Coat unsaturated polyester for composites
Trade name	POLYCOR ISO BR;POLYCOR QCC ISO BR 0400;POLYCOR QCC ISO BR LV 0400;POLYCOR ISO BR LV;POLYCOR ISO BR LV2;POLYCOR ISO BR HV;POLYCOR ISO PTY;POLYCOR ISO BR FC;POLYCOR ISO BR IHB;POLYCOR ISO BR AD;POLYCOR TOPCOAT ISO BR;POLYCOR TOPCOAT QCC ISO BR LV 0400;POLYCOR ISO BR FC AD;POLYCOR TOPCOAT ISO BR FC;POLYCOR TOPCOAT ISO BR HAR;POLYCOR TOPCOAT ISO BR LV;POLYCOR ISO BR LV AD;POLYCOR ISO BR LV FC;POLYCOR TOPCOAT ISO BR HV;POLYCOR ISO BR LV IHB;POLYCOR TOPCOAT ISO BR LV IHB;POLYCOR TOPCOAT ISO BR IHB;POLYCOR TOPCOAT ISO BR LV FC;POLYCOR TOPCOAT ISO BR LV2;POLYCOR ISO BR LV3;POLYCOR TOPCOAT BR LV2;POLYCOR TOPCOAT BR LV3;POLYCOR TOPCOAT ISO 9116 TM BR HAR;POLYCOR TOPCOAT ISO 9132 TM BR HAR
Pure substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	To form a protective and decorative layer for GRP composites. Contact us before using for food contact application.
------------------------	---

1.3. Details of the supplier of the safety data sheet

Supplier	Polynt Composites France S.A. Route d'Arras CS 50019 62320 Drocourt France Tel : +33 3 21 74 84 00 Fax : +33 3 21 49 55 84
-----------------	---

Manufacturer

Polynt Composites France S.A.
Route d'Arras CS 50019
62320 Drocourt
France
Tel : +33 3 21 74 84 00
Fax : +33 3 21 49 55 84

Polynt Composites Spain, S.L.
Avenida República Argentina S/N
09200 Miranda de Ebro - Burgos
Tel : (+34) 947 027 202
Fax : (+34) 947 31 45 40

Polynt Composites Poland Sp. z o.o.
ul. Grabska 11d, 32-005 Niepołomice, Polska
+48 12 281 42 00/+48 12 281 42 01

Polynt Composites Stallingborough UK Ltd.
Laporte Road
Stallingborough - Near Grimsby
North East Lincolnshire DN41 8DR
Tel : (+44) 1469 552 570
Fax : (+44) 1469 552 597

For further information, please contact

E-mail address Rccp.SDSmanagement@polynt.com
Internet Address <http://www.polynt.com>

1.4. Emergency telephone number

This telephone number is available 24 hours per day, 7 days per week.	
Europe, America, Middle East, Africa (European language countries) :	+44 (0) 1235 239 670
Middle East/Africa (Arabic speaking countries) :	+44 (0) 1235 239 671
Asia Pacific :	+65 3158 1074

Poison Information Centre telephone number

European emergency phone number : 112
UK : National Poisons Emergency Number : 0845 4647
Ireland : National Poisons Information Centre (NPIC) Telephone Healthcare Professionals : +353 (01) 809 2566. (24 hour service) Telephone Members of Public : +353 (01) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week)

SECTION 2: Hazards identification2.1. Classification of the substance or mixtureClassification of the substance or mixture - GHS/CLP (n° 1272/2008)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific Target Organ Toxicity (Single Exposure)	Category 3
Specific target organ toxicity - repeated exposure	Category 1
Chronic Aquatic Toxicity	Category 3
Flammable liquids	Category 3

2.2. Label elements

Contains Styrene

**Signal word****Danger****Hazard statements**

H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H335 - May cause respiratory irritation
 H361d - Suspected of damaging the unborn child
 H372 - Causes damage to organs through prolonged or repeated exposure if inhaled
 H412 - Harmful to aquatic life with long lasting effects
 H226 - Flammable liquid and vapour

Physical hazards

EU H -Phrases

EUH208 Contains cobalt octoate - May produce an allergic reaction.

Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P243 - Take precautionary measures against static discharge
 P260 - Do not breathe vapour
 P273 - Avoid release to the environment
 P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection
 P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight percent	GHS Classification
Styrene	202-851-5	01-2119457861-32	100-42-5	~ 39	Flam. Liq. 3 (H226) Repr. 2 (H361d) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Asp. Tox. 1 (H304) STOT SE 3 (H335) STOT RE 1 (H372) Aquatic Chronic 3 (H412)
Titanium dioxide	236-675-5	01-2119489379-17	13463-67-7	~ 17	-
glass, oxide, chemicals	266-046-0	No data available	65997-17-3	~ 10	-
Talc	238-877-9	No data available	14807-96-6	~ 8	-
Barium sulfate	231-784-4	01-2119491274-35	7727-43-7	~ 4	-

Silica, amorphous, fumed, crystalline-free	231-545-4	01-2119379499-16	112945-52-5	~ 3	-
Naphtha (petroleum), hydrodesulfurized heavy	265-185-4	01-2119490979-12	64742-82-1	~ 0.5	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) STOT SE 3 (H336) Aquatic Chronic 2 (H411)
(2-methoxymethylethoxy)propanol	252-104-2	01-2119450011-60	34590-94-8	~ 0.3	Acute Tox. 4 (H332)
Potassium 2-ethylhexanoate	221-625-7	01-2119980714-29	3164-85-0	~ 0.1	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Repr. 2 (H361)
cobalt octoate	205-250-6	01-2119524678-29	136-52-7	< 0.25	Skin Sens. 1 (H317) Eye Irrit. 2 (H319) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 3 (H412)

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance Do not breathe dust/fume/gas/mist/vapours/spray
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. If symptoms persist, call a physician
Skin contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes If skin irritation persists, call a physician
Inhalation	Move to fresh air If not breathing, give artificial respiration Consult a physician
Ingestion	Do NOT induce vomiting Rinse mouth. Consult a physician
Protection of first-aiders	Use personal protective equipment See section 8 for more information

4.2. Most important symptoms and effects, both acute and delayed

Eye Contact	Irritating to eyes
Skin contact	Irritating to skin May produce an allergic reaction.
Inhalation	Harmful: danger of serious damage to health by prolonged exposure through inhalation Irritating to respiratory system
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician No information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Dry chemical, Foam, Carbon dioxide (CO₂), (closed systems)

Extinguishing Media Which Must not be Used for Safety Reasons Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases Vapours may form explosive mixtures with air. Most vapours are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Heating or fire can release toxic gas : Carbon monoxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Personal precautions

Remove all sources of ignition
Heat, flames and sparks.
Take precautionary measures against static charges.
Ensure adequate ventilation
Use personal protective equipment

For emergency responders

Avoid breathing vapours or mists In the event of fire and/or explosion do not breathe fumes. Use personal protective equipment

6.2. Environmental precautions

Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.
Do not flush into surface water or sanitary sewer system

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13)
Use clean non-sparking tools to collect absorbed material

6.4. Reference to other sections

See section 8 for more information
See Section 12 for additional Ecological Information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Avoid static electricity build up with connection to earth Use only in area provided with appropriate exhaust ventilation In case of insufficient ventilation, wear suitable respiratory equipment For personal protection see section 8
Prevention of fire and explosion	Keep away from open flames, hot surfaces and sources of ignition Do not use compressed air for filling, discharging or handling. Empty containers may contain flammable or explosive vapours
Hygiene measures	When using, do not eat, drink or smoke Provide regular cleaning of equipment, work area and clothing Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep in a dry, cool and well-ventilated place. Keep at temperature not exceeding 30°C Keep away from heat and sources of ignition.
Materials to avoid	Strong oxidizing agents, Catalyst, Peroxides, Reducing agents
Packaging material	metallic GRP Tanks (Reinforced Glass Polyester)
Unsuitable materials for containers	copper, Copper alloys, Bronze, Zinc

7.3. Specific end use(s)

Specific use(s)	No information available
------------------------	--------------------------

SECTION 8: Exposure controls/personal protection8.1. Control parametersOccupational Exposure limits

Chemical Name	European Union	ACGIH OEL (Ceiling)	The United Kingdom	Ireland
Styrene 100-42-5	-	TLV-8h TWA: 20 ppm - 85 mg/m ³ TLV-15min STEL: 40 ppm - 170 mg/m ³	STEL 250 ppm STEL 1080 mg/m ³ TWA 100 ppm TWA 430 mg/m ³	TWA 20 ppm TWA 85 mg/m ³ STEL 40 ppm STEL 170 mg/m ³
Titanium dioxide 13463-67-7		TWA 10 mg/m ³	STEL 30 mg/m ³ STEL 12 mg/m ³ TWA 10 mg/m ³ TWA 4 mg/m ³	TWA 10 mg/m ³ TWA 4 mg/m ³
Talc 14807-96-6		TWA 2 mg/m ³	STEL 3 mg/m ³ TWA 1 mg/m ³	TWA 10 mg/m ³ TWA 0.8 mg/m ³
Barium sulfate 7727-43-7	TWA 0.5 mg/m ³	TWA 10 mg/m ³	STEL 30 mg/m ³ STEL 12 mg/m ³ STEL 1.5 mg/m ³ TWA 10 mg/m ³ TWA 4 mg/m ³ TWA 0.5 mg/m ³	TWA 2 mg/m ³ TWA 0.5 mg/m ³
(2-methoxymethylethoxy)propanol 34590-94-8	TWA 50 ppm TWA 308 mg/m ³ S*	TWA 100 ppm	STEL 150 ppm STEL 924 mg/m ³ TWA 50 ppm TWA 308 mg/m ³ Skin	TWA 50 ppm TWA 308 mg/m ³ Skin
cobalt octoate 136-52-7		0.02 mg/m ³	STEL 0.3 mg/m ³ TWA 0.1 mg/m ³ Sen+	TWA 0.1 mg/m ³ Sensitizer

Special hazards arising from the substance or mixtureBiological standards**Derived No Effect Level (DNEL)**

Derived No Effect Level (DNEL)
Styrene (100-42-5)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Systemic effect		406 mg/Kg bw/day	85 mg/m ³	
Workers - Acute Short Term - Local effect			306 mg/m ³	
Workers - Acute Short term - Systemic effect			289 mg/m ³	
General Population - Acute Short Term - Local effect			182.7 mg/m ³	
General Population - Acute Short Term - Systemic effect			174.2 mg/m ³	
General Population - Long Term - Systemic effect	2.1 mg/Kg bw/day	343 mg/Kg bw/day	10.2 mg/m ³	

Titanium dioxide (13463-67-7)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Local effect			10 mg/m ³	
General Population - Long Term - Systemic effect	700 mg/kg bw/day			

Barium sulfate (7727-43-7)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Systemic effect			10 mg/m ³	
General Population - Long Term - Systemic effect	13000 mg/kg bw/day		10 mg/m ³	

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Systemic effect			4 mg/m ³	

(2-methoxymethylethoxy)propanol (34590-94-8)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Systemic effect		283 mg/kg bw/day	308 mg/m ³	
General Population - Long Term - Systemic effect	36 mg/kg bw/day	121 mg/kg bw/day	37.2 mg/m ³	

Potassium 2-ethylhexanoate (3164-85-0)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Systemic effect		12 mg/kg bw/day	32 mg/m ³	
Workers - Long Term - Systemic effect	2.5 mg/kg bw/day	6 mg/kg bw/day	8 mg/m ³	

cobalt octoate (136-52-7)

Type	DNEL oral	DNEL dermal	DNEL inhalation	Remark
Workers - Long Term - Local effect			235.1 µg/m ³	
General Population - Long Term - Systemic effect	55.8 µg/kg bw/day			
General Population - Long Term - Local effect			37 µg/m ³	

Predicted No Effect Concentration (PNEC)

PNEC Component		
Styrene (100-42-5)		
Exposure	Type	PNEC
Fresh water	PNEC Aqua	0.028 mg/L
Marine water	PNEC Aqua	0.014 mg/L
Intermittent use/release	PNEC Aqua	0.04 mg/L
Fresh water	PNEC Sediment	0.614 mg/Kg.dw
Marine water	PNEC Sediment	0.307 mg/Kg.dw
Terrestrial Compartment	PNEC Soil	0.2 mg/Kg.dw
STP microorganisms	PNEC STP	5 mg/L

Titanium dioxide (13463-67-7)		
Exposure	Type	PNEC
Fresh water	PNEC Aqua	0.127 mg/L
Marine water	PNEC Aqua	1 mg/L
Intermittent use/release	PNEC Aqua	0.61 mg/L
	PNEC STP	100 mg/L
Fresh water	PNEC Sediment	1000 mg/kg sediment dw
Marine water	PNEC Sediment	100 mg/kg sediment dw
	PNEC Soil	100 mg/kg soil dw
Secondary Poisoning	PNEC Oral	1667 mg/kg food

Barium sulfate (7727-43-7)		
Exposure	Type	PNEC
Fresh water	PNEC Aqua	227.8 mg/L
	PNEC STP	50.1 mg/L
Fresh water	PNEC Sediment	792.7 mg/kg sediment dw
	PNEC Soil	207.7 mg/kg soil dw

Silica, amorphous, fumed, crystalline-free (112945-52-5)		
Exposure	Type	PNEC
Secondary Poisoning	PNEC Oral	60000 mg/kg

(2-methoxymethylethoxy)propanol (34590-94-8)		
Exposure	Type	PNEC
Marine water	PNEC Aqua	1.9 mg/L
Fresh water	PNEC Aqua	19 mg/L
Intermittent use/release	PNEC Aqua	190 mg/L
	PNEC STP	4168 mg/L
Fresh water	PNEC Sediment	70.2 mg/kg sediment dw
Marine water	PNEC Sediment	7.02 mg/kg sediment dw
	PNEC Soil	2.74 mg/kg soil dw

Potassium 2-ethylhexanoate (3164-85-0)		
Exposure	Type	PNEC
Marine water	PNEC Aqua	0.036 mg/L
Fresh water	PNEC Aqua	0.36 mg/L
Intermittent use/release	PNEC Aqua	0.493 mg/L
	PNEC STP	71.7 mg/L
Fresh water	PNEC Sediment	6.37 mg/kg sediment dw
Marine water	PNEC Sediment	0.637 mg/kg sediment dw
	PNEC Soil	1.06 mg/kg soil dw

cobalt octoate (136-52-7)		
Exposure	Type	PNEC
Fresh water	PNEC Aqua	0.6 µg/L
Marine water	PNEC Aqua	2.36 µg/L
STP microorganisms	PNEC STP	0.37 mg/L
Fresh water	PNEC Sediment	9.5 mg/kg sediment dw
Marine water	PNEC Sediment	9.5 mg/kg sediment dw

Terrestrial Compartment	PNEC Soil	10.9 mg/kg soil dw
-------------------------	-----------	--------------------

8.2. Exposure controls

Occupational exposure controls

Engineering measures

Apply technical measures to comply with the occupational exposure limits.
When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment

Personal protective equipment

General Information

Use personal protective equipment.

Respiratory protection

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour)
If exposure limits are likely to be exceeded / In case of insufficient ventilation wear suitable respiratory equipment :

Breathing apparatus with filter Type A (Organic gases and vapours filter conforming to EN 14387 , APF 40 < 1 hour, APF 200 > 1 hour) / Type A(2)/P3 in combination with Particulates filter conforming to EN 143 , if exposed to dust

Eye protection

Safety glasses with side-shields. Do not wear contact lenses.

Skin and body protection

Antistatic boots. Protective shoes or boots. Wear fire/flame resistant/retardant clothing.

Hand protection

Wear chemically resistant gloves (tested to EN 374) in combination with 'basic' employee training

Glove material : Neoprene , Nitriles , Viton (R) or Polyvinyl alcohol

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Environmental exposure controls

Environmental exposure controls Do not allow material to contaminate ground water system.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

<u>Property</u>	<u>Values</u>	<u>Remark</u>
Appearance	Variable (This Data Sheet includes all the colours)	
Physical state	Liquid	
Particle size		no data available
Odour	Styrene	
Odour Threshold	0.15 ppm	Values related to styrene
pH		no data available
pH (as aqueous solution)		no data available
Melting point/range	- 30 °C	Values related to styrene
Freezing Point		no data available
Boiling point	145 °C	Values related to styrene
Flash point	31 °C	Values related to styrene
Evaporation rate		no data available
Flammability Limits in Air		
upper	6,1 - 6,8%	Values related to styrene
lower	0,9 - 1,1%	Values related to styrene
Vapour pressure	6.52 mbar	20°C
Vapour density	3.6	Values related to styrene
Density	1.1 - 1.4 g/cm3	20°C
Water solubility	Insoluble in water	
Partition coefficient: n-octanol/water	3	Values related to styrene
Autoignition temperature	490 °C	Values related to styrene
Decomposition temperature		no data available
Viscosity, kinematic	15455 - 27273 mm2/s	20°C
Viscosity, dynamic	17000 - 30000 mPa.s	20°C
Explosive properties		not applicable
Oxidizing properties		not applicable

9.2. Other information

<u>Property</u>	<u>Values</u>	<u>Remark</u>
Solubility in other solvents	Soluble in most organic solvents	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product may ignite and burn at temperatures exceeding the flash point

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions In use, may form flammable/explosive vapour-air mixture.

Hazardous polymerisation Polymerisation can occur.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.
Exposure to light.
Take precautionary measures against static charges.

10.5. Incompatible materials

Materials to avoid Strong oxidizing agents, Catalyst, Peroxides, Reducing agents

10.6. Hazardous decomposition products

Hazardous decomposition products Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects**Acute toxicity**

Inhalation Harmful: danger of serious damage to health by prolonged exposure through inhalation
Irritating to respiratory system

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	Read-across (Analogy)
Styrene 100-42-5	5000 mg/kg (Rat)	> 2000 mg/kg bw (Rat) 24h OECD 402	11.8 mg/L (Rat) 4h CSR	
Titanium dioxide 13463-67-7	> 5000 mg/kg bw (Rat) OECD 425	> 10000 mg/kg (Rabbit)	> 6,82 mg/L air (Rat) 4h	
glass, oxide, chemicals 65997-17-3	2000 - 5000 mg/kg (estimated)	> 5000 mg/kg (estimated)		
Barium sulfate 7727-43-7	> 5000 mg/kg bw (Rat) OECD 401	> 2000 mg/kg bw (Rat) OECD 408 Read across with Cas N° : 10361-37-2		
Silica, amorphous, fumed, crystalline-free 112945-52-5	> 5000 mg/kg bw (Rat) OECD 401	> 5000 mg/kg (Rabbit)	> 0.14 mg/L air (Rat) 4h (analytical) OECD 403	
(2-methoxymethylethoxy)pr opanol 34590-94-8	> 5000 mg/kg bw (Rat) Similar to OECD 401	9510 mg/kg bw(Rabbit) 24h Similar to OECD 402	LC0 (7h) > 275 ppm (1667 mg/m ³) (Rat) Similar to OECD 403	

Potassium 2-ethylhexanoate 3164-85-0	2043 mg/kg bw (Rat) OECD 401	> 2000 mg/kg bw (Rat) OECD 402	LC0 = 0.11 mg/L air (Rat, vapour) 8h OECD 436 Read across with 2-ethylhexanoic acid Cas N° : 149-57-5	
cobalt octoate 136-52-7	3129 mg/kg/bw (Rat) OECD 425			

Skin corrosion/irritation

Chemical Name	Skin corrosion/irritation	Read-across (Analogy)
Styrene 100-42-5	Irritating to skin in vivo assay rabbit	
Titanium dioxide 13463-67-7	No skin irritation No skin corrosion in vivo assay rabbit OECD 404	
Barium sulfate 7727-43-7	No skin irritation in vitro study OECD Guidelines for Testing of Chemicals + Commission regulation (EC) No. 440/2008 B.46	barium dichloride dihydrate Cas N° : 10326-27-9
Silica, amorphous, fumed, crystalline-free 112945-52-5	No skin irritation rabbit OECD 404	
(2-methoxymethylethoxy)propanol 34590-94-8	No skin irritation in vivo assay rabbit similar to OECD 404	
Potassium 2-ethylhexanoate 3164-85-0	Irritating to skin in vivo assay rabbit OECD 404	
cobalt octoate 136-52-7	No skin corrosion OECD 431 EU Method B. 40	

Serious Eye Damage/Eye Irritation

Chemical Name	Serious Eye Damage/Eye Irritation	Read-across (Analogy)
Styrene 100-42-5	Irritating to eyes in vivo assay rabbit	
Titanium dioxide 13463-67-7	No eye irritation in vivo assay rabbit OECD 405	
Barium sulfate 7727-43-7	No eye irritation in vivo assay rabbit OECD 405	
Silica, amorphous, fumed, crystalline-free 112945-52-5	No eye irritation rabbit OECD 405	
(2-methoxymethylethoxy)propanol 34590-94-8	No eye irritation in vivo assay	
Potassium 2-ethylhexanoate 3164-85-0	Ambiguous in vitro study Bovine OECD 437 EU Method B.47	
cobalt octoate 136-52-7	Moderate eye irritation OECD 437 EU Method B.47 Irritating to eyes rabbit OECD 405	

Respiratory or skin sensitisation May produce an allergic reaction.

Chemical Name	Respiratory or skin sensitisation	Read-across (Analogy)
Styrene 100-42-5	Does not cause skin sensitization Does not cause respiratory sensitization CSR	
Titanium dioxide 13463-67-7	Does not cause skin sensitization in vivo assay guinea pig OECD 406 mouse OECD 429	
Barium sulfate 7727-43-7	Does not cause skin sensitization in vivo assay mouse OECD 429	barium dichloride dihydrate Cas N° : 10326-27-9
Silica, amorphous, fumed, crystalline-free 112945-52-5	Does not cause skin sensitization Does not cause respiratory sensitization	
(2-methoxymethylethoxy)propanol 34590-94-8	Does not cause skin sensitization in vivo assay	
Potassium 2-ethylhexanoate 3164-85-0	Does not cause skin sensitization in vivo assay guinea pig OECD 406	2-ethylhexanoic acid Cas N° : 149-57-5
cobalt octoate 136-52-7	May cause sensitisation by skin contact	

Mutagenic Effects

in vitro study

Chemical Name	Ames test	Read-across (Analogy)
Styrene 100-42-5	Ambiguous In vitro gene mutation study in bacteria (S. typhimurium G46, TA1530, TA 1535, TA100, TA98, TA1538, TA 1537) OECD 471	
Titanium dioxide 13463-67-7	negative In vitro gene mutation study in bacteria OECD 471	
Barium sulfate 7727-43-7	negative In vitro gene mutation study in bacteria (S. typhimurium TA 1535, TA 1537, TA 98 and TA 100) OECD 471	barium dichloride dihydrate Cas N° : 10326-27-9
Silica, amorphous, fumed, crystalline-free 112945-52-5	negative In vitro gene mutation study in bacteria OECD 471	
(2-methoxymethylethoxy)propanol 34590-94-8	negative In vitro gene mutation study in bacteria (Escherichia coli WP2 uvrA) similar to OECD 471	
Potassium 2-ethylhexanoate 3164-85-0	negative In vitro gene mutation study in bacteria (S. typhimurium TA 1535, TA 1537, TA 98 and TA 100) OECD 471	2-ethylhexanoic acid Cas N° : 149-57-5

Chemical Name	In vitro Mammalian Cell Gene Mutation Test	Read-across (Analogy)
Styrene 100-42-5	Ambiguous In vitro gene mutation study in mammalian cells hamster OECD 476	
Titanium dioxide 13463-67-7	negative In vitro gene mutation study in mammalian cells mouse OECD 476	

Barium sulfate 7727-43-7	negative In vitro gene mutation study in mammalian cells mouse OECD 476	barium dichloride dihydrate Cas N° : 10326-27-9
Silica, amorphous, fumed, crystalline-free 112945-52-5	negative In vitro gene mutation study in mammalian cells OECD 476	
(2-methoxymethylethoxy)propanol 34590-94-8	negative In vitro gene mutation study in mammalian cells rat similar to OECD 482	
Potassium 2-ethylhexanoate 3164-85-0	negative In vitro gene mutation study in mammalian cells mouse hamster OECD 476 EPA OTS 798.5300	2-ethylhexanoic acid Cas N° : 149-57-5
Chemical Name	In vitro Mammalian Chromosome Aberration Test	Read-across (Analogy)
Styrene 100-42-5	positive Chromosome aberration test in vitro OECD 473 OECD 479	
Titanium dioxide 13463-67-7	negative Chromosome aberration test in vitro hamster OECD 473	
Barium sulfate 7727-43-7	negative Chromosome aberration test in vitro hamster OECD 473	barium dichloride dihydrate Cas N° : 10326-27-9
Silica, amorphous, fumed, crystalline-free 112945-52-5	negative Chromosome aberration test in vitro OECD 473	
(2-methoxymethylethoxy)propanol 34590-94-8	negative Chromosome aberration test in vitro hamster similar to OECD 473	
Potassium 2-ethylhexanoate 3164-85-0	negative Chromosome aberration test in vitro OECD 473	2-ethylhexanoic acid Cas N° : 149-57-5

in vivo assay

Chemical Name	Unscheduled DNA Synthesis (UDS)	Read-across (Analogy)
Styrene 100-42-5	negative mouse OECD 486 OECD 474	
Titanium dioxide 13463-67-7	negative mouse	
Silica, amorphous, fumed, crystalline-free 112945-52-5	negative rat	
Potassium 2-ethylhexanoate 3164-85-0	negative mouse OECD 474	
cobalt octoate 136-52-7	negative rat OECD 474 OECD 475	

Carcinogenicity**Carcinogenicity****Styrene (100-42-5)**

Exposure routes	Method	Species	Dose	Evaluation
Inhalation	OECD 453	rat	NOAEC systemic (carcinogenicity) >= 4.34 mg/L air (nominal)	negative

Inhalation	OECD 453	mouse	LOAEC (carcinogenicity) female/male = 0.09 - 0.18 mg/L air resp., NOAEC (carcinogenicity) male = 0.09 mg/L air	positive
Oral	No information available	rat	NOAEL (carcinogenicity) >= 2000 mg/kg bw /day	positive
Oral	No information available	mouse	LOAEL (carcinogenicity) = 150 mg/kg bw /day	positive

Titanium dioxide (13463-67-7)

Exposure routes	Method	Species	Dose	Evaluation
Inhalation	OECD 453	rat	NOAEC lung tumours = 5 mg/m ³ air	negative
Oral	No information available	rat	NOEL toxicity > 50000 ppm (nominal)	negative

Barium sulfate (7727-43-7)

Exposure routes	Method	Species	Dose	Evaluation
Oral	Read across with barium dichloride dihydrate Cas N° : 10326-27-9	rat	NOAEL carcinogenicity (male) = 60 mg/kg bw/day NOAEL carcinogenicity (female) = 75 mg/kg bw/day	negative

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Exposure routes	Method	Species	Dose	Evaluation
Oral	OECD 453	rat	NOAEL = 1800 - 3200 mg/kg bw/day	negative

Reproductive toxicity**Reproductive toxicity****Styrene (100-42-5)**

Exposure routes	Method	Species	Dose	Evaluation
Inhalation	No information available	rat	NOAEL/LOAEL (fertility) 60d = 100 - 200 mg/kg bw/day	positive
Oral	OECD 422	rat	NOAEL/LOAEL (fertility) 60d = 200 - 400 mg/kg bw/day	positive
Inhalation	OECD 416	rat	NOAEC (P, F1) = 0.64 mg/L air LOAEC (P, F1) = 2.13 mg/L air NOAEC (F2) = 0.21 mg/L air LOAEC (F2) = 0.64 mg/L air (70d)	negative

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Exposure routes	Method	Species	Dose	Evaluation
Oral	OECD 415	rat	NOAEL = 497 mg/kg bw/day	negative

Potassium 2-ethylhexanoate (3164-85-0)

Exposure routes	Method	Species	Dose	Evaluation
Oral	Read-across (Analogy) 2-ethylhexanoic acid Cas N° : 149-57-5	rat	NOAEL (fertility) = 300 mg/kg bw/day	negative

Developmental Toxicity Suspected of damaging the unborn child.**Developmental Toxicity****Styrene (100-42-5)**

Exposure routes	Method	Species	Dose	Evaluation
-----------------	--------	---------	------	------------

Inhalation	No information available	rat	NOAEC/LOAEC (maternal toxicity + developmental toxicity) >50d = 1.08 - 2.15 mg/L air	positive
Inhalation	OECD 414	rat	LOAEC (maternal toxicity) 6-15d = 1.28 mg/L air	positive
Inhalation	OECD 414	rat	NOAEC (developmental toxicity) 6-15d >= 2.56 mg/L air	negative
Inhalation	OECD 414	rabbit	NOAEC (maternal toxicity + developmental toxicity) 6-18d = 2.56 mg/L air	negative

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Exposure routes	Method	Species	Dose	Evaluation
Oral	OECD 414	rat	NOAEL (maternal toxicity) = 1350 mg/kg bw/day NOAEL (teratogenicity) = 1350 mg/kg bw/day	negative

(2-methoxymethylethoxy)propanol (34590-94-8)

Exposure routes	Method	Species	Dose	Evaluation
Inhalation	EPA OTS 798.4350	rat	NOAEL (maternal tox/teratogenicity) 6-15d = 300 ppm	negative

Potassium 2-ethylhexanoate (3164-85-0)

Exposure routes	Method	Species	Dose	Evaluation
Oral	Read-across (Analogy) 2-ethylhexanoic acid Cas N° : 149-57-5	rat	NOAEL (maternal toxicity) = 300 mg/kg bw/day LOAEL (teratogenicity) = 100 mg/kg bw/day	negative

Specific target organ toxicity - single exposure May cause irritation of respiratory tract

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure , target organ(s) : Central nervous system , Ears

STOT - repeated exposure**Styrene (100-42-5)**

Exposure routes	Method	Species	Dose	Remarks
Inhalation	OECD 412	rat mouse	NOAEC male (28d) = 3.47 mg/L air NOAEC (ototoxicity) 28d = 2.13 mg/L air NOAEC (28d) = 0.181 mg/L air NOAEC (28d) = 0.688 mg/L air	
Inhalation	No information available	rat	NOAEC (nasal tract) = 0.85 mg/L air NOAEC (overall) = 2.13 mg/L air NOAEC (ototoxicity) = 0.85 mg/L air LOAEC (ototoxicity) = 3.41 mg/L air NOAEC (overall) = 2.13 mg/L air	
Oral	No information available	rat	NOAEL (toxicity) = 1000 mg/kg bw/day LOAEL (toxicity) = 2000 mg/kg bw/day	

Oral	No information available	mouse	NOAEL (toxicity) = 150 mg/kg bw /day LOAEL (toxicity) = 300 mg/kg bw /day	
Inhalation	OECD 453	rat	LOAEC local (toxicity) = 0.21 mg/L air	

Titanium dioxide (13463-67-7)

Exposure routes	Method	Species	Dose	Remarks
Oral	OECD 407	rat	NOEL (29d) = 24000 mg/kg bw/day	
Inhalation	No information available	rat	NOEC (carcinogenicity) = 50 mg/m ³ air NOEC (non-neoplastic changes) = 10 mg/m ³ air	

Barium sulfate (7727-43-7)

Exposure routes	Method	Species	Dose	Remarks
Oral	Read-across (Analogy) Cas N°: 10326-27-9	rat	NOAEL = 104 mg/kg bw/day	

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Exposure routes	Method	Species	Dose	Remarks
Oral	OECD 408	rat	NOEL (highest dose) 4000 <= 4500 mg/kg bw/day 90d	
Inhalation	OECD 413	rat	NOEC = 1.3 mg/m ³ air NOEC < 1.3 mg/m ³ air 90d	
Dermal	No information available	rabbit	NOAEL >= 10000 mg/kg bw/day	

(2-methoxymethylethoxy)propanol (34590-94-8)

Exposure routes	Method	Species	Dose	Remarks
Oral	KANPOGYO No.700, YAKUHATSU No. 1039.61 and KIKYKU No. 1014	rat	NOEL/NOAEL (4 weeks) = 200/1000 mg/kg	
Inhalation	similar to OECD 413	rat	NOAEL (13 weeks) = 200 ppm	
Dermal	similar to OECD 411	rabbit	NOAEL (90d) = 2850 mg/kg bw/day	

Potassium 2-ethylhexanoate (3164-85-0)

Exposure routes	Method	Species	Dose	Remarks
Oral	Read-across (Analogy) Cas N°: 149-57-5 TSCA	rat	NOAEL (male) = 61 mg/kg/day NOAEL (female) = 71 mg/kg/day	
Oral	No information available	mouse	NOAEL (male) = 180 mg/kg/day NOAEL (female) = 205 mg/kg/day	

cobalt octoate (136-52-7)

Exposure routes	Method	Species	Dose	Remarks
Oral	Read-across (Analogy) Cas N°: 13586-84-0 OECD 422	rat	NOAEL (female) = 5 mg/kg bw/day NOAEL (male) = 40 mg/kg bw/day	

Aspiration hazard

Due to the viscosity, this product does not present an aspiration hazard.

Other information

None

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not flush into surface water or sanitary sewer system

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Styrene 100-42-5	LC50 (72h) = 4.9 mg/L (Pseudokirchnerella subcapitata) EPA OTS 797.1050	EC50 (48h) = 4.7 mg/L (Daphnia magna) NOEC = 1.9 mg/L (Daphnia magna) OECD 202	LC50 (96h) = 4.02 - 10 mg/L (Pimephales promelas) OECD 203	EC (30min) = 500 mg/L (Activated sludge of a predominantly domestic sewage) OECD 209
Titanium dioxide 13463-67-7	EC50 (72h) > 10000 mg/L (Skeletonema costatum) ISO 10253	LC50 (48h) = 20000 mg/L (Daphnia magna)	EC50 (96h) > 100 mg/L (Brachydanio rerio) LC50 (96h) > 1000 mg/L (Fundulus heteroclitus) LC0 (48h) > 1000 mg/L (Leuciscus idus) OECD 203	EC50 (3h) > 1000 mg/L, NOEC (3h) >= 1000 mg/L (Activated sludge of a predominantly domestic sewage) OECD 209
Talc 14807-96-6			LC50 (96h) = 100 g/L (Brachydanio rerio)	
Barium sulfate 7727-43-7	EC50 (72h) > 100 mg/L (Pseudokirchnerella subcapitata) NOEC (72h) = 100 mg/L (Pseudokirchnerella subcapitata) OECD 201	EC50 (48h) = 14500 µg/L (Daphnia magna)	LC50 (96h) > 97.5 mg/L (Danio rerio) OECD 203	EC50 (3h) > 1000 mg/L (activated sludge of a predominantly domestic sewage) NOEC (3h) >= 1000 mg/L (activated sludge of a predominantly domestic sewage) OECD 209
Silica, amorphous, fumed, crystalline-free 112945-52-5		EL50 (24h) >= 1000 mg/L (Daphnia magna) OECD 202	LC50 (96h) > 10000 mg/L (Brachydanio rerio) OECD 203	
(2-methoxymethylethoxy)propanol 34590-94-8	EC50 (72h) > 969 mg/L (Pseudokirchnerella subcapitata) OECD 201	LC50 (48h) = 1919 mg/L (Daphnia magna) Similar to OECD 202	LC50 (96h) > 1000 mg/L (Poecilia reticulata) OECD 203	EC10 (18h) = 4168 mg/L (Pseudomonas putida) No guideline followed
Potassium 2-ethylhexanoate 3164-85-0	EC50 (72h) = 49.3 mg/L (Desmodesmus subspicatus) OECD 201 Read across with 2-ethylhexanoic acid Cas N° : 149-57-5	EC50 (48h) = 910 mg/L (Daphnia magna) OECD 202 Read across with Cas N° : 16977-89-3	LC50 (96h) > 100 mg/L (Oryzias latipes) OECD 203 Read across with Cas N° : 16766-89-3	EC50 (17h) = 112.1 mg/L, EC10 (17h) = 71.7 mg/L (Pseudomonas putida) DIN 38412, part 8
cobalt octoate 136-52-7	EC50 cell number yield (72h) = 283.1 µg/L EC50 growth rate (72h) = 654.2 µg/L NOEC (72h) = 150.6 µg/L (Pseudokirchnerella subcapitata) OECD 201			

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
---------------	-------------------	--	------------------	----------------------------

Styrene 100-42-5		NOEC (21d) = 1.01 mg/L (Daphnia magna) LOEC (21d) = 2.06 mg/L (Daphnia magna) EC50 (21d) = 1.88 mg/L (Daphnia magna) OECD 203		
Titanium dioxide 13463-67-7	NOEC (72h) = 5600 mg/L (Skeletonema costatum) ISO 10253	NOEC (48h) >= 3 mg/L (Daphnia magna) OECD 202, OECD 209		
Barium sulfate 7727-43-7		NOEC (21d) = 2900 µg/L (Daphnia magna) ECHA methodology (i.e., EC16/2)		
(2-methoxymethylethoxy)pr opanol 34590-94-8		NOEC (22d) >= 0.5 mg/L (Daphnia magna) Similar to OECD 211		
Potassium 2-ethylhexanoate 3164-85-0		NOEC (21d) = 25 mg/L (Daphnia magna) OECD 211		
cobalt octoate 136-52-7	NOEC/EC10 (freshwater, 7d) mortality = 86.4 µg/L and reproduction = 19.7 - 20.1 µg/L (Ceriodaphnia dubi)			

Effects on terrestrial organisms - Component Information

Chronic toxicity				
Styrene (100-42-5)				
Chronic toxicity	Method	Species	Values	Remarks
Toxicity to invertebrates	OECD 207	Eisenia foetida	LC50 (14d) = 120 mg/kg soil dw LOEC (burrowing time and mean percent weight change) = 65 mg/kg soil dw LOEC (survival) = 180 mg/kg soil dw NOEC (mean percent weight change) = 34 mg/kg soil dw	
(2-methoxymethylethoxy)propanol (34590-94-8)				
Chronic toxicity	Method	Species	Values	Remarks
plants	OECD 227	Grossypium hirsutum	NOEC (21d) = 250 g/L	

12.2. Persistence and degradability

Chemical Name	Biodegradation	Evaluation
Styrene 100-42-5	87% (20d) similar to OECD 301D	Readily biodegradable
(2-methoxymethylethoxy)propanol 34590-94-8	96 % (28d) DOC removal, 75 % (10d) OECD 301F	Readily biodegradable
Potassium 2-ethylhexanoate 3164-85-0	> 70 % (99%) (28d), Read across with benzoic acid, sodium salt OECD 301E	Readily biodegradable
cobalt octoate 136-52-7	60% (> 10d), OECD 301 B	Readily biodegradable

12.3. Bioaccumulative potential

Bioconcentration factor (BCF)		
Styrene (100-42-5)		
Method	Species	Bioconcentration factor (BCF)
Calculation method		74

Titanium dioxide (13463-67-7)		
Method	Species	Bioconcentration factor (BCF)
no data available	Oncorhynchus mykiss	20 L/kg (14d)

Barium sulfate (7727-43-7)		
Method	Species	Bioconcentration factor (BCF)
no data available	Lepomis macrochirus	74.4 L/kg

Chemical Name	log Pow
Styrene 100-42-5	3
(2-methoxymethylethoxy)propanol 34590-94-8	0.0043
Potassium 2-ethylhexanoate 3164-85-0	2.96

12.4. Mobility in soil

Chemical Name	LogKoc	Koc
Styrene 100-42-5	2.55	352

12.5. Results of PBT and vPvB assessment

Chemical Name	PBT	vPvB
Styrene 100-42-5	This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	This substance is not considered to be very persistent nor very bioaccumulating (vPvB).
Titanium dioxide 13463-67-7	This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	This substance is not considered to be very persistent nor very bioaccumulating (vPvB).
Silica, amorphous, fumed, crystalline-free 112945-52-5	This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	This substance is not considered to be very persistent nor very bioaccumulating (vPvB).
(2-methoxymethylethoxy)propanol 34590-94-8	This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Autres effets néfastes

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products Dispose of in accordance with the European Directives on waste and hazardous waste. Do not flush into surface water or sanitary sewer system

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Other information According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

14.1. UN number

ADR/RID	UN1866
IMDG/IMO	UN1866
ICAO/IATA	UN1866

ADN UN1866

14.2. UN proper shipping name

ADR/RID

Resin solution
UN1866, RESIN SOLUTION, 3, PG III, (D/E)

IMDG/IMO

Resin solution
UN1866, RESIN SOLUTION, 3, PG III, (31°C c.c.)

ICAO/IATA

UN1866, RESIN SOLUTION, 3, PG III

ADN

Resin solution
UN1866, RESIN SOLUTION, 3, PG III14.3. Transport hazard class(es)

ADR/RID

Hazard class 3

IMDG/IMO

Hazard class 3

ICAO/IATA

Hazard class 3

ADN

Hazard class 314.4. Packing group

ADR/RID III

IMDG/IMO III

ICAO/IATA III

ADN III

14.5. Environmental hazards

ADR/RID No

IMDG/IMO No

Marine pollutant No

ICAO/IATA No

ADN No

14.6. Special precautions for user

ADR/RID

Classification Code F1
Tunnel restriction code (D/E)
Limited quantity 5 L

IMDG/IMO

EmS F-E, S-E
Limited quantity 5 L

ICAO/IATA

ERG Code 3L
Limited quantity 10 L

ADN

Classification Code F1
Limited quantity 5 L

ventilation VE01

Special precautions for users

Special precautions No information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk according to MARPOL 73/78 and the IBC Code not applicable

SECTION 15: Regulatory information

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP]

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Chemical Name	96/82/EC (SEVESO) - §9	96/82/EC (SEVESO) - §6, §7
Styrene - 100-42-5	50000	5000 tonnes 50000 tonnes

National regulatory information

The United Kingdom

Avoid exceeding of the given occupational exposure limits (see section 8).

Ireland

Avoid exceeding of the given occupational exposure limits (see section 8).

15.2. Chemical safety assessment

not applicable

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child if inhaled
H361d - Suspected of damaging the unborn child
H361f - Suspected of damaging fertility
H372 - Causes damage to organs through prolonged or repeated exposure if inhaled
H400 - Very toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects
EUH208 - May produce an allergic reaction

Training Advice

Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the instructions for use.

Sources of key data used to compile the datasheet

ECHA

Former date 30-Nov-2016

Revision date 08-Sep-2017

Revision Note

SDS sections updated : 1 , 3 , 8 , 11 , 12

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet