

Technical Data Sheet

IB15800A White ISO Medium Viscous Brushing Gelcoat

Description

White, isophthalic brushing polyester gelcoat (medium viscosity)

Product use

General purpose, high quality moulding gelcoat for hand lay-up in GRP work.

Characteristics

For brush application, free from air & drainage, With excellent opacity & whiteness. The product exhibits excellent weathering properties and water resistance.

Application

IB15643A should be used in workshop temperatures between 18 - 25°C and requires the addition of 2% medium activity MEKP for a sufficient cure. For best results, the gelcoat should be applied to a clean dry polished mould in one even layer 400 – 500 microns (0.4 – 0.5 mm) thickness. Before use, the temperature of the gelcoat should be 18 - 25°C.

Liquid gelcoat properties

Appearance : White, opaque air free liquid
Liquid properties : Thixotropic
Gel time : < 15 minutes
(2% medium active
MEKP @ 25°C)



PREMIUM QUALITY

All of our products are manufactured to the highest standards, working to our ISO 9001:2015 system and are amongst the best in the world.



FAST SUPPLY

We have a choice of standard and next day services on both hazardous and non-hazardous freight. We also have our own fleet of vans and freight forward options to truly offer national coverage.



TECHNICAL BACKUP

We offer more than just a technical data sheet. We advise and explain any technical aspect to ensure peace of mind when ordering from Colorplas. We form partnerships with our clients and nothing is too much trouble to ensure that you have all the information you need to order the product most suited to your application.



CUSTOMER SUPPORT

We love beating expectations and we pride ourselves on customer service. So if you're unhappy with your current gelcoat and pigment paste specialist manufacturing company



CONTACT US

Colorplas Ltd,
Moss Bridge Road
Rochdale,
OL16 5PQ
UK
www.colorplas.com
+44 (0) 1706 351888
info@colorplas.com

